



Description

Application: In turning of pipes and tubes which cannot be held by ordinary Live Centers because of small point diameters of live centers.

Not suitable for CNC turning applications.

60 Degree angle Revolving Cone (Not Dead)

Dead Pipe Centers for grinding application (recommended) made against order.

Bearings protected from coolant & dirt / chips by oil seal.

Part No.	Shank Taper	Ød mm	ØD mm	ØD1 mm	L mm	L1 mm	Conc. Error mm	Max. RPM
PC MT2 25-50	MT-2	25	55	17.780	64.0	65.0	0.015	750
PC MT2 30-65	MT-2	30	65	17.780	64.0	66.0	0.015	750
PC MT2 40-75	MT-2	40	77	17.780	64.0	69.0	0.015	600
PC MT3 25-50	MT-3	25	55	23.825	81.0	65.0	0.015	750
PC MT3 30-65	MT-3	30	65	23.825	81.0	66.0	0.015	750
PC MT3 40-75	MT-3	40	77	23.825	81.0	69.0	0.015	600
PC MT3 50-90	MT-3	50	90	23.825	81.0	70.0	0.015	600
PC MT3 65-100	MT-3	65	102	23.825	81.0	70.0	0.015	500
PC MT3 35-125	MT-3	35	127	23.825	81.0	133.5	0.015	350
PC MT3 75-125	MT-3	75	127	23.825	102.5	98.5	0.015	350
PC MT4 25-50	MT-4	25	55	31.267	102.5	67.5	0.015	750
PC MT4 30-65	MT-4	30	65	31.267	102.5	68.5	0.015	750

Part No.	Shank Taper	Ød mm	ØD mm	ØD1 mm	L mm	L1 mm	Conc. Error mm	Max. RPM
PC MT4 40-75	MT-4	40	77	31.267	102.5	70.5	0.015	600
PC MT4 50-90	MT-4	50	90	31.267	102.5	71.5	0.015	600
PC MT4 65-100	MT-4	65	102	31.267	102.5	71.5	0.015	500
PC MT4 35-125	MT-4	35	127	31.267	102.5	128.0	0.015	350
PC MT4 75-125	MT-4	75	127	31.267	102.5	93.0	0.015	350
PC MT4 75-150	MT-4	75	153	31.267	102.5	98.0	0.015	300
PC MT4 100-175	MT-4	100	178	31.267	102.5	128.0	0.015	250
PC MT4 100-200	MT-4	100	204	31.267	102.5	128.0	0.015	250
PC MT5 25-50	MT-5	25	55	44.399	129.5	67.5	0.015	750
PC MT5 30-65	MT-5	30	65	44.399	129.5	68.5	0.015	750
PC MT5 40-75	MT-5	40	77	44.399	129.5	71.5	0.015	600
PC MT5 50-90	MT-5	50	90	44.399	129.5	72.5	0.015	600
PC MT5 65-100	MT-5	65	102	44.399	129.5	72.5	0.015	500
PC MT5 35-125	MT-5	35	127	44.399	129.5	129.5	0.015	350
PC MT5 75-125	MT-5	75	127	44.399	129.5	94.5	0.015	350
PC MT5 75-150	MT-5	75	153	44.399	129.5	99.0	0.015	300
PC MT5 100-175	MT-5	100	178	44.399	129.5	128.0	0.015	250
PC MT5 100-200	MT-5	100	204	44.399	129.5	128.0	0.015	250
PC MT5 100-230	MT-5	100	231	44.399	129.5	145.0	0.015	200
PC MT5 200-275	MT-5	200	275	44.399	129.5	135.5	0.015	150
PC MT6 65-100	MT-6	65	102	63.348	182.0	85.0	0.015	500
PC MT6 35-125	MT-6	35	127	63.348	182.0	131.0	0.015	350
PC MT6 75-125	MT-6	75	127	63.348	182.0	96.0	0.015	350
PC MT6 75-150	MT-6	75	153	63.348	182.0	101.0	0.015	300
PC MT6 100-175	MT-6	100	178	63.348	182.0	123.5	0.015	250
PC MT6 100-200	MT-6	100	204	63.348	182.0	123.5	0.015	250
PC MT6 100-230	MT-6	100	231	63.348	182.0	140.0	0.015	200
PC MT6 200-275	MT-6	200	275	63.348	182.0	130.0	0.015	150