



Description

Application: In turning of pipes and tubes which cannot be held by ordinary Live Centers because of small point diameters of live centers.

Not suitable for CNC turning applications.

60 Degree angle Revolving Cone (Not Dead).

Dead Pipe Centers for grinding application (recommended) made against order.

Bearings protected from coolant & dirt / chips by oil seal.

Part No.	Shank Taper	ØD mm	ØD1 mm	L mm	L1 mm	Conc. Error mm	Max. RPM
PC MT2 0-2"	MT-2	55	17.780	64.0	88.0	0.015	750
PC MT2 0-2½"	MT-2	65	17.780	64.0	91.0	0.015	750
PC MT2 0-3"	MT-2	77	17.780	64.0	102.0	0.015	600

Part No.	Shank Taper	ØD mm	ØD1 mm	L mm	L1 mm	Conc. Error mm	Max. RPM
PC MT3 0-2"	MT-3	55	23.825	81.0	88.0	0.015	750
PC MT3 0-2½"	MT-3	65	23.825	81.0	91.0	0.015	750
PC MT3 0-3"	MT-3	77	23.825	81.0	102.0	0.015	600
PC MT3 0-3½"	MT-3	90	23.825	81.0	115.0	0.015	600
PC MT3 0-4"	MT-3	102	23.825	81.0	115.0	0.015	500
PC MT3 0-5"	MT-3	127	23.825	81.0	163.5	0.015	350
PC MT4 0-2"	MT-4	55	31.267	102.5	90.5	0.015	750
PC MT4 0-2½"	MT-4	65	31.267	102.5	93.5	0.015	750
PC MT4 0-3"	MT-4	77	31.267	102.5	103.5	0.015	600
PC MT4 0-3½"	MT-4	90	31.267	102.5	116.5	0.015	600
PC MT4 0-4"	MT-4	102	31.267	102.5	116.5	0.015	500
PC MT4 0-5"	MT-4	127	31.267	102.5	158.0	0.015	350
PC MT5 0-2"	MT-5	55	44.399	129.5	90.5	0.015	750
PC MT5 0-2½"	MT-5	65	44.399	129.5	93.5	0.015	750
PC MT5 0-3"	MT-5	77	44.399	129.5	104.5	0.015	600
PC MT5 0-3½"	MT-5	90	44.399	129.5	117.5	0.015	600
PC MT5 0-4"	MT-5	102	44.399	129.5	117.5	0.015	500
PC MT5 0-5"	MT-5	127	44.399	129.5	159.0	0.015	350
PC MT6 0-4"	MT-6	102	63.348	182.0	130.0	0.015	500
PC MT6 0-5"	MT-6	127	63.348	182.0	161.0	0.015	350


[Download e-brochure \(http://tummax.in/downloads.html\)](http://tummax.in/downloads.html) (to know quickly more about us download our corporate brochure)